

This is a quick reference specification sheet, full details can be found in the Gas 320 / 620 ACE installation/service guide via remeha.co.uk/documents.

Gas 620⁺ 1300

TECHNICAL SPECIFICATION SHEET

December 2020

OVERVIEW

MODEL : Gas 620 - 1300	CE: 0063CU3937
Rated Output kW (80/60°C)	165.4 - 1201.7
Rated Output kW (50/30°C)	1303
Weight (dry) kgs	1099
Overall Dim W x H x D	1442 x1550 x 2172
No of sections:	2 X 10
SBEM - Efficiency GCV (1)	95.66
Efficiency Full Load 100%: NCV(4)	98.5
Efficiency Part Load 30%: NCV(5)	108.1
Stand-by Heat Loss W * :	1074

BURNER TYPE PRE MIX

Std Fuel Available	Natural Gas
Fuel Consumption M3/h	129.1 NG max
Fuel Consumption M3/h LPG	Not Available
Flame Protection	Ionisation
Ignition	Electronic
Noise level dB(A) at 1 metre	67.8
Optional Fuel	Not Available
LGP adjustment (*)	Not Available
Gas Connection size BSP	2" (M) per module
Min/Max Gas pressure mbar	17 - 25
NOx annual emissions EN15502*****	47 mg/kWh
NOx annual emissions BREEAM*****	18 mg/kWh

FLUE/AIR INLET

Flue diameter mm I/D	350
Air inlet diameter mm I/D	250 / 350*
Mass flue gas flow rate kg/hr	286 - 2054
Flue gas temperature °C	30 - 65
Maximum counter pressure PA	150

CONTROLS/OPTIONS

Standard Controls: SCB-01 provides two volt free contacts for status notification, 0-10v connection for PWM system pump. SCB-02 provides functionality for a DHW and central heating zone. Gateway GTW-22 provides functionality to connect a boiler to an app via bluetooth.
--

ERP DATA - ECO DESIGN

Useful Efficiency - Full Load (GCV)%	NA Above 400kW ErP
Useful Efficiency - Part Load (GCV)%	NA Above 400kW ErP
Sound Power Levels Lwa Indoors dB	NA Above 400kW ErP

HYDRAULICS

Water Content Litres	104 per module
Resistance @ 11°C mbar	435 (43.5kPA) per module
Resistance @ 20°C mbar	130 (13kPA) per module
Nom Flow Rate @ 11°C l/s	13.0 per module
Nom Flow Rate @ 20°C l/s	7.1 per module
Condensate Connection	32mm per module
Flow Connection PN10	DN80 Flanged per module
Return Connection PN10 **	DN80 Flanged per module
Std Operating Temp °C ***	20-90 ***
Max Operating Temp °C	90
High Limit Set Point °C	110
Max operating pressure bar	7
Min operating pressure bar	1
Sealed System Only.	

ELECTRICAL

Power Supply	230v - 1ph - 50hz X 2
Power Consumption W	20 - 1440
Fuse Rating amps (Main)	10 AT per module
Fuse Rating CB-01	6.3 AT per module
Fuse Rating CU-GH	1.6 AT per module
Controls Voltage	24 (max 4va)
Insulation Class IP	X1

(1) In accordance with the Non Domestic Building Services Compliance Guide 2013 Edition-For use in England. * With optional Insulation Kit.

** Important The return flange connection is DN80 however, the inner bore of the return flange is DN65. If fitting a butterfly valve or similar please ensure a spool piece is first fitted to avoid the valve fouling the inner bore of the DN65 bore of the return flange.

*** Important When operating above the 25K dT (Parameters GP021) the boiler will restrict the maximum operating temperature to 80 deg C.

**** 350mm air inlet supplied as standard.

***** NOx emissions with standard factory settings G20 EN15502.

***** NOx emissions set to BREEAM settings at commissioning G20 EN15502.