

REMTANK⁺

SINGLE COIL 300l

TECHNICAL
SPECIFICATION
SHEET

APRIL 2020

This is a quick reference specification sheet. Full details can be found in the installation/service guide via remeha.co.uk/documents.

MODEL:

Storage Volume (litres)	291
Max Working/Pressure (bar)	8

ErP DATA:

Standing Loss (kWh/24h)	1.49
Standing Loss (W)	74
ErP Energy Class	C

CONNECTIONS:

Primary Flow Connection (Inch/BSP)	1"
Primary Return Connection (Inch/BSP)	1"
Secondary Return (Inch/BSP)	1"
Inlet Connection (Inch/BSP)	1"
Outlet Connection (Inch/BSP)	1"
Drain Connection (Inch/BSP)	1"

UNVENTED KIT:

UNVENTED KIT NOT SUPPLIED WITH CYLINDER: 7726936

CYLINDER DATA:

Primary Coil Rate at Maximum (kW)	49
Primary Coil Rate at Max (litre/min)	100
Heat Up Time (max)	45 minutes
Lower Coil Surface Area m ²	N/A
Upper Coil Surface Area m ²	1.4
Maximum Pressure in Coil (bar)	25

MODEL DIMENSIONS:

Weight Full (kg)	376
Weight Empty (kg)	85
Insulation Thickness (mm)	60
Height of Cylinder (mm)	1685
Diameter of Cylinder (mm)	620
Service Clearance:	
Front (mm)	250
Sides (mm)	250
Above (mm)	250
Shipping:	
Width (mm)	680
Depth (mm)	680
Height (mm)	1940
Weight (kg)	95

NOTES:

Factory Fitted temperature & pressure relief valve set at 90°C / 10 bar

REMTANK⁺

SINGLE COIL 500l

TECHNICAL
SPECIFICATION
SHEET

APRIL 2020

This is a quick reference specification sheet, full details can be found in the installation/service guide via remeha.co.uk/documents.

MODEL:

Storage Volume (litres)	484
Max Working/Pressure (bar)	8

ErP DATA:

Standing Loss (kWh/24h)	2.42
Standing Loss (W)	101
ErP Energy Class	C

CONNECTIONS:

Primary Flow Connection (Inch/BSP)	1"
Primary Return Connection (Inch/BSP)	1"
Secondary Return (Inch/BSP)	1"
Inlet Connection (Inch/BSP)	1"
Outlet Connection (Inch/BSP)	1"
Drain Connection (Inch/BSP)	1"

UNVENTED KIT:

UNVENTED KIT NOT SUPPLIED WITH CYLINDER: 7726937

CYLINDER DATA:

Primary Coil Rate at Maximum (kW)	61
Primary Coil Rate at Max (litre/min)	100
Heat Up Time (max)	50
Lower Coil Surface Area m ²	N/A
Upper Coil Surface Area m ²	1.8
Maximum Pressure in Coil (bar)	25

MODEL DIMENSIONS:

Weight Full (kg)	601
Weight Empty (kg)	117
Insulation Thickness (mm)	60
Height of Cylinder (mm)	1690
Diameter of Cylinder (mm)	770
Service Clearance:	
Front (mm)	250
Sides (mm)	250
Above (mm)	250
Shipping:	
Width (mm)	820
Depth (mm)	820
Height (mm)	1920
Weight (kg)	127

NOTES:

Factory Fitted temperature & pressure relief valve set at 90°C / 10 bar

REMTANK⁺

SINGLE COIL 800

TECHNICAL
SPECIFICATION
SHEET

APRIL 2020

This is a quick reference specification sheet, full details can be found in the installation/service guide via remeha.co.uk/documents.

MODEL:

Storage Volume (litres)	769
Max Working/Pressure (bar)	8

ErP DATA:

Standing Loss (kWh/24h)	2.60
Standing Loss (W)	108
ErP Energy Class	C

CONNECTIONS:

Primary Flow Connection (Inch/BSP)	1"
Primary Return Connection (Inch/BSP)	1"
Secondary Return (Inch/BSP)	1.5"
Inlet Connection (Inch/BSP)	1.25"
Outlet Connection (Inch/BSP)	1.5"
Drain Connection (Inch/BSP)	1.25"

UNVENTED KIT:

UNVENTED KIT NOT SUPPLIED WITH CYLINDER: 7726938

CYLINDER DATA:

Primary Coil Rate at Maximum (kW)	83
Primary Coil Rate at Max (litre/min)	133
Heat Up Time (max)	52
Lower Coil Surface Area m ²	N/A
Upper Coil Surface Area m ²	2.8
Maximum Pressure in Coil (bar)	25

MODEL DIMENSIONS:

Weight Full (kg)	933
Weight Empty (kg)	164
Insulation Thickness (mm)	80
Height of Cylinder (mm)	1840
Diameter of Cylinder (mm)	950
Service Clearance:	
Front (mm)	250
Sides (mm)	250
Above (mm)	250
Shipping:	
Width (mm)	1000
Depth (mm)	1000
Height (mm)	2040
Weight (kg)	184

NOTES:

Factory Fitted temperature & pressure relief valve set at 90°C / 10 bar

REMTANK⁺

SINGLE COIL 1000

TECHNICAL
SPECIFICATION
SHEET

APRIL 2020

This is a quick reference specification sheet. Full details can be found in the installation/service guide via remeha.co.uk/documents.

MODEL:

Storage Volume (litres)	955
Max Working/Pressure (bar)	8

ErP DATA:

Standing Loss (kWh/24h)	3.38
Standing Loss (W)	141
ErP Energy Class	C

CONNECTIONS:

Primary Flow Connection (Inch/BSP)	1"
Primary Return Connection (Inch/BSP)	1"
Secondary Return (Inch/BSP)	1.5"
Inlet Connection (Inch/BSP)	1.25"
Outlet Connection (Inch/BSP)	1.5"
Drain Connection (Inch/BSP)	1.25"

UNVENTED KIT:

UNVENTED KIT NOT SUPPLIED WITH CYLINDER: 7726939

CYLINDER DATA:

Primary Coil Rate at Maximum (kW)	115
Primary Coil Rate at Max (litre/min)	133
Heat Up Time (max)	58
Lower Coil Surface Area m ²	N/A
Upper Coil Surface Area m ²	3.4
Maximum Pressure in Coil (bar)	25

MODEL DIMENSIONS:

Weight Full (kg)	1144
Weight Empty (kg)	189
Insulation Thickness (mm)	80
Height of Cylinder (mm)	2250
Diameter of Cylinder (mm)	950
Service Clearance:	
Front (mm)	250
Sides (mm)	250
Above (mm)	250
Shipping:	
Width (mm)	1000
Depth (mm)	1000
Height (mm)	2040
Weight (kg)	214

NOTES:

Factory Fitted temperature & pressure relief valve set at 90°C / 10 bar