

QUINTA⁺ ACE 55

TECHNICAL SPECIFICATION SHEET

March 2020

This is a quick reference specification sheet, full details can be found in the Quinta ACE installation/service guide via remeha.co.uk/documents

Technical Information from Quinta Ace Installation and User Manual NOT7684359 - v06 - 10012019

OVERVIEW

MODEL : Quinta ACE 55	GC No : N/A
Rated Output kW (80/60°C)	55.3
Rated Output kW (50/30°C)	58.6
Weight (dry) kgs	56 (without front panel)
Overall Dim WxHxD mm	500x750x500
No of sections:	One piece casting
SBEM Seasonal Efficiency %: GCV ⁽¹⁾	96.04
Efficiency - Full Load 100%: NCV ⁽⁴⁾	97.8
Efficiency - Part Load 30%: NCV ⁽⁵⁾	108.7
Stand-by Heat Loss kW :	0.110

BURNER TYPE PRE MIX

Std Fuel Available	Natural Gas
Fuel Consumption M ³ /h	6.0 NG max
Fuel Consumption M ³ /h	2.3 LPG max
Flame Protection	Ionisation
Ignition	Electronic
Noise level dB(A) at 1 metre	46.7
Optional Fuel	Propane
LGP adjustment (*)	
Gas Connection size BSP	3/4" (M)
Min/Max Gas pressure mbar	17-25 NG
Min/Max Gas pressure mbar	37-50 LPG
NOx (Dry, 0% O ₂) NCV - EN15502	36 Mg/kWh (Class 6)

CONCENTRIC FLUE/AIR INLET

Flue diameter mm I/D	100
Air inlet diameter mm I/D	150
Mass flue gas flow rate kg/hr	19-93
Flue gas temperature °C	30-68
Maximum counter pressure PA	120

CONTROLS/OPTIONS

<p>STANDARD -</p> <ul style="list-style-type: none"> On/Off, 0-10v dc, Open Therm, R-Bus High limit protection and low water protection Volt free common alarm and boiler run indication Manual o/ride Hot water priority facility (3 way valve or pump) Two Safety Interlocks Hours run indication Flue - concentric connection (***) (#) 	<p>OPTIONAL - Optimising compensators for single and multiple boilers</p> <ul style="list-style-type: none"> Cascade kits - multiple boiler pipework kits Low loss headers Outside sensor fir simple weather compensation Hot water priority kits - pump or valve kits Relay kits for single and multiple controls - 230v switching relay
--	--

ERP DATA ENERGY LABEL

Seasonal Space Efficiency % ⁽²⁾	92
Energy Efficiency Class ⁽²⁾	A
Sound Power Levels Lwa Indoors dB	55
Annual Energy Consumption Gj	173
Useful Efficiency - Full Load (GCV)% ⁽³⁾	88.1
Useful Efficiency - Part Load (GCV)% ⁽³⁾	97.9

HYDRAULICS

Water contents ltrs	6.4
Resistance @ 11°C mbar	430
Resistance @ 20°C mbar	130
Nom Flow Rate @ 11° C l/s	1.20
Nom Flow Rate @ 20° C l/s	0.66
Min Flow Rate m ³ /hr	0.4
Condensate Connection	3/4" OD
Connection Size " BSP	1 1/4" (M)
Std Operating Temp °C	20-90(**)
Max Operating Temp °C	90 (**)
High Limit Set Point °C	110 (**)
Max operating pressure bar	4
Min operating pressure bar	0.8
Min operating pressure bar	0.3 o/v

ELECTRICAL

Power Supply	230v - 1 ph - 50hz
Start Current amps	1.8
Power Consumption W	38 - 100
Modulating input V dc	0-10
Fuse Rating amps	2.5
Controls Voltage	24 (max 4va)
Insulation Class IP	X4D

(1) In accordance with the Non Domestic Building Services Compliance Guide 2013 Edition-For use in England

(2) In accordance with EU 811 & 812 / 2013 Energy Labeling Regulations

(3) In accordance with EU 813 & 814 / 2013 Eco Design Regulations

(4) @ 80/60 °C Nett (EN 92/42) EEC

(5) @ 50/30 °C nett (92/42) EEC

(*) See installation and service manual

(**) Open vented option maximum operating temperature 75°C high limit 95°C

(***) For conventional or room sealed operation

(#) Flue adaptor available for CLV systems